

# EKI-6558TI

# EKI-6559TMI

**8-port M12 IP67 Managed Industrial Ethernet Switch with Wide Temperature**

**8-port M12 + 2-port Fiber Optic IP67 Managed Industrial Ethernet Switch with Wide Temperature**

**NEW**



## Features

- Backplane (Switching Fabric): 2 Gbps
- Supports X-Ring function (ultra high-speed recovery time <10ms)
- Wide redundant power design
- Provides M12 connector with IP67 protection
- Provides Waterproof fiber optic connector
- TFTP firmware updates and system configure restore and backup
- Dual 12 ~ 48 V<sub>DC</sub> power input and 1 relay output
- Supports wide operating temperature -40~ 75° C
- Provides 100Mbps LC type connector

## Introduction

EKI-6558TI and EKI-6559TMI are cost effective IP67 grade industrial switches. M12 connectors secure highly reliable connectivity for industrial communication applications. EKI-6559TMI provides two additional fiber optic ports to extend communication range. Both EKI-6558TI and EKI-6559TMI provide Advantech's X-Ring protocol, which enables users to establish a redundant Ethernet network with ultra high-speed recovery (less than 10ms). They also support advanced network standards to optimize network performance, reduce maintenance cost, and secure network safety.

## Specifications

### Communications

- **Standard** IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ad, IEEE802.1d, IEEE802.1w, IEEE802.1p, IEEE802.1Q, IEEE802.1x
- **LAN** 10/100Base-T(X), 100Base-FX
- **Transmission Speed** Up to 100Mbps

### Interface

- **Ethernet** M12, 4-pole D-coded, Female x 8
- **Fiber Optic** LC type waterproof x 2
- **Console** M12, 8-pole A-coded, Female x 1

### Network Management

- **Configuration** Web browser, Telnet, Serial console, TFTP, SNMPv1/v2c/v3, Port Speed/Duplex Configuration
- **VLAN** IEEE 802.1Q, GVRP, Port-based VLAN
- **Redundancy** Advantech X-Ring (Recovery time < 10ms at 30pcs full loading ring structure), Dual Homing, Couple Ring, 802.1w/D RSTP/STP
- **Security** IP Access security, port security, DHCP Server, Port and IP Binding, 802.1X Port Access Control
- **Traffic Control** IGMP Snooping/Query for multicast group management Port Trunking, Static/802.3ad LACP Rate limit and storm control IEEE 802.1p QoS CoS/TOS/DSCP priority queuing IEEE 802.3x flow control Port Mirroring, Real-time traffic statistic, MAC Address Table, SNMP, Syslog, Email Alert, SNMP Trap, RMON
- **Diagnostics**

### Mechanism

- **Enclosure** IP67, aluminum shell with solid mounting kits
- **Dimensions (W x H x D)** 193 x 176 x 62.5 mm
- **Mounting** Wallmount

### Power

- **Power Consumption** 8.1W Max. @ 48 V<sub>DC</sub>
- **Power Input** 12 ~ 48 V<sub>DC</sub>, redundant dual inputs
- **Power Connector** M12, 5-pole A-coded, male x 1
- **P-Fail Output** 1A @ 24 V<sub>DC</sub>
- **P-Fail Connector** M12, 8-pole A-coded, Female x 1

### Protection

- **Power Reverse** Present

### Environment

- **Operating Temperature** -40 ~ 75° C (-40 ~ 167° F)
- **Storage Temperature** -40 ~ 85° C (-40 ~ 185° F)
- **Operating Humidity** 5 ~ 95% (non-condensing)
- **Storage Humidity** 0 ~ 95% (non-condensing)

### Certifications

- **Safety** UL 508
- **EMC** EU: EN55011, EN61000-6-4  
EN55022 Class A, EN61000-3-2/3  
EN55024, IEC61000-4-2/3/4/5/6/8  
EN61000-6-2
- **Shock** IEC60068-2-27
- **Freefall** IEC60068-2-32
- **Vibration** IEC60068-2-6

### Ordering Information

- **EKI-6558TI** 8-port M12 IP67 Managed Ethernet Switch
- **EKI-6559TMI** 8-port M12 + 2 Fiber IP67 Managed Ethernet Switch